

TECHNICAL INFORMATION SHEET

QuickSeam™ Batten Cover

Item Description

6" (152.4 mm) x 100' (30.5 m)
9" (228.6 mm) x 100' (30.5 m)
12" (304.8 mm) x 50' (15.2 m)

Item Number

W56RAC1616
W56RAC1619
W56RAC1624



Product Information

Description:

QuickSeam Batten Cover is a semi-cured EPDM and QuickSeam Tape laminate designed to cover and seal batten strips and as specified by Firestone Specifications and Details.

Method of Application:

1. Use QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime the roofing components within the seaming area.
2. Center and apply the QuickSeam Batten Cover over the batten strip.
3. Refer to application instructions for specifics: www.firestonebpc.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures

Precautions:

Refer to Safety Data Sheet (SDS).

LEED® Information:

Post-Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR
*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



TECHNICAL INFORMATION SHEET

QuickSeam™ Batten Cover

Packaging:

- 6" (152.4 mm) Roll - 2 rolls per carton – 36 cartons per pallet
- 9" (228.6 mm) Roll - 1 roll per carton – 36 cartons per pallet
- 12" (304.8 mm) Roll - 1 roll per carton – 36 cartons per pallet

Typical Properties

QUICKSEAM TAPE		EPDM FLASHING	
Property	Value	Property	Value
Base	Rubber Polymers	Base	EPDM
Color	Black	Color	Black
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Specific Gravity	98 ± 0.02 (H ₂ O = 1)	Cured State	Semi-Cured
Cured State	Cured	Thickness	0.040" (1.016 mm) ± 0.017" - 0.007"
Thickness	0.035" (0.89 mm) ± 0.005" (0.127 mm)	Width	6" (152.4 mm) + 0, - 0.125" (3.175 mm)
Width	6.125" (155.6 mm) + 9.5 mm, - 0"		

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.