

TECHNICAL INFORMATION SHEET

UltraPly™ TPO QuickSeam™ 9½" Flashing

**Description**

White
Gray
Tan

Item Number

W56TPO30T9
W56TPOG0T9
W56TPOT0T9

Product Information

Description:

UltraPly TPO QuickSeam 9½" Flashing is an unsupported (non-reinforced) TPO membrane factory laminated to white seam tape. UltraPly TPO QuickSeam 9½" Flashing is used to flash gravel stops and other flashing applications as indicated in Firestone specifications and details.

Method of Application:

1. Use Firestone Single Ply QuickPrime™ Primer or Single Ply LVOC Primer applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces to receive UltraPly QuickSeam 9 1/2" Flashing.
2. Refer to current Firestone specifications for application instructions and details using Firestone UltraPly TPO QuickSeam 9 1/2" Flashing: www.firestonebpc.com
3. Note: UltraPly TPO QuickSeam products must be heat-formed to conform to seam step-offs, metal laps, angle changes, etc.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 1.5 years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

Refer to Safety Data Sheet (SDS).

LEED® Information:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Michigan Center, MI
*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



TECHNICAL INFORMATION SHEET

UltraPly™ TPO QuickSeam™ 9½" Flashing

Packaging	
Property	Value
Roll:	9.5" (235 mm) x 100' (30.48 m) roll
Carton:	1 roll per carton

NOTES: QuickScrubber and/or QuickScrubber Plus Pads and Handles are included in each carton. Quantities vary depending on the QuickSeam product.

Typical Properties

QUICKSEAM TAPE		TPO UNSUPPORTED FLASHING	
Property	Value	Property	Value
Base:	Rubber Polymers	Base:	TPO
Color:	White	Color:	White, Gray, Tan
Percent Solids:	100%	Solvents:	None
Specific Gravity:	1.08 ± 0.03	Percent Solids:	100%
Cured State:	Cured	Specific Gravity:	0.96 ± 0.02
Thickness:	0.030" (0.76 mm) ± .005" (0.13 mm)	Thickness:	0.030"(0.76 mm) ± 10%
Width:	9¾" (248 mm) -0 /+ 1/16" (1.6 mm)	Width:	9½" (241 mm) +0 / - ¼" (3.18 mm)
Length:	100' (30.5 m)	Length:	100' (30.5 m)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.