

# TECHNICAL INFORMATION SHEET

## QuickSeam™ Splice Tape

**Item Description**

3" X 100' (76.2 mm x 30.5 m)  
 4" X 100' (101.6 mm x 30.5 m)  
 6" X 100' (152.4 mm x 30.5 m)  
 7" X 100' (177.8 mm x 30.5 m)

**Item Number**

W56RAC1603  
 W56RAC160A  
 W56RAC1626  
 W56RAC1617

### Product Information

**Description:**

Firestone 3" (76.2 mm), 4" (101.6 mm) 6" (152.4 mm) and 7" (177.8 mm) QuickSeam Splice Tape is designed for field splicing of RubberGard™ EPDM membrane panels and flashing.

**Method of Application:**

1. Use QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime Primer or Single-Ply QuickPrime LVOC and a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to Firestone Specifications and Details.
3. Refer to application instructions for specifics: [www.firestonebpc.com](http://www.firestonebpc.com).

**Storage:**

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

**Shelf Life:**

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

**Precautions:**

Refer to Safety Data Sheet (SDS) for further information.

**LEED® Information:**

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Prescott, AR

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



# TECHNICAL INFORMATION SHEET

## QuickSeam™ Splice Tape

### Typical Properties

Property	Value
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.025" (0.63 mm) ± 0.003" (0.076 mm)
Roll	3" (76.3 mm) x 100' (30.5 m) roll, 6 rolls per carton 4" (101.6 mm) x 100' (30.5 m) roll, 4 rolls per carton 6" (152.4 mm) x 100' (30.5 m) roll, 2 rolls per carton 7" (177.8 mm) x 100' (30.5 m) roll, 2 rolls per carton
Pallet	40 cartons per pallet

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*